



| SAE Number | Commercial Grade | NTA Number | Color | Nominal Wool | Actual Wool | Density (1"), Lbs./Sq Yd | Standard Thickness Range, in. |
|------------|------------------|------------|-------|--------------|-------------|--------------------------|-------------------------------|
| F-1 | 16R1 | 34R1 | White | 100% | 95% | 16 | 1/8 to 1 |
| F-2 | 16R2 | 34R2 | Pink | 100% | 90% | 16 | 1/8 to 1 |
| F-3 | 16R3 | 34R3 | Grey | 95-100% | 85% | 15.6 | 1/8 to 1 |
| F-5 | 12R1 | 26R1 | White | 100% | 95% | 12.24 | 1/8 to 1 |
| F-6 | | 26R2 | Grey | | 87% | 12.24 | 1/8 to 1 |
| F-7 | 12R3 | 26R3 | Grey | 85-95% | 80% | 12.24 | 1/8 to 1 |
| F-10 | 9R1 | 18R1 | White | 100% | 95% | 8.48 | 1/8 to 1 |
| F-11 | 9R2 | 18R2 | Grey | 95-100% | 87% | 8.48 | 1/8 to 1 |
| F-12 | | --- | Grey | | 85% | 8.48 | 1/8 to 1 |
| F-13 | 9R4 | 18R3 | Grey | 80-85% | 75% | 8.48 | 1/8 to 1 |
| F-15N | 9R5 | --- | Grey | 60-65% | 55% | 8.48 | 1/8 to 1 |
| F-26N | 8R5 | 17R2 | Grey | 50-55% | 45% | 7.2 | 1/8 to 1 |
| F-50 | 16R1X | 34R1 | White | 100% | 95% | 15.6 | 3/64 to 3/32 |
| F-51 | 16R3X | 34R3 | Grey | 100% | 92% | 15.6 | 3/64 to 3/32 |
| F-55 | 12R3X | 26R3 | Grey | 80-85% | 75% | 12 | 1/16 to 3/32 |
| F-55B | | | Black | 80-85% | 75% | 12 | 1/16 to 3/32 |